BOE-THERM



Present our latest Temperature Control Unit "One"





Technical specifications for a ONE

1	ec	hn	ical	S	p	e	ci	fi	C	a	ti	01	าร	

Max outlet temperature	90 °C					
Heating capacity	9 kW					
Heat transfer fluid	Water					
Tank volumen	10 Liter					
Pump	std.					
Type	TM6					
Flow rate max. I/min	60					
Pressure max. Bar	3,5					
Power kW	0,5					
Cooling capacity at $\Delta T = 60$ °C						
Type	12					
kW	33					
Connections in/out	1/2"					
Operating voltage std.	3x400V/50Hz					
Dimensions (L x W x H)	535 x 270 x 540 mm					

€ 1.975, -

Our well proven Water Temperature Control Unit have been upgraded with a brandnew Touch-Screen control.

The Temp series is available in 90,95,120,140 and 160° with a variety of pumps and heating capacities.

Contact our sales department for quotion or if you have further questions regarding our Temperature Control Units

pd@boe-therm.dk

NEW Mark VI controller

- Touch-Screen Displays the actual value and set point simultaneously.
- Variable information on the display
 Choose additional value to be displayed on the screen (Flow, pressure or heat/cool ratio)
- Easy operation
 Intuitive structure in the operation menu
- Ramp programing
 As a standard feature the ramp programming makes heating and cooling in cycle an easy operation
- Remote access via Webserver Fully operational via a smart device or PC



3.5" Touch-Screen



Standard

- 3.5" color Touch-Screen controller
 Self-optimizing temperature control via microprocessor
- Multiple language
- Ramp program
- * Alarm log
- ❖ Common acoustic alarm
 - Service interval indicator
 - USB interface
- Remote access via LAN and webserver

Options

- Flow measurement External sensor PT 100
- Communications interfaces
- FlushingLeak stop
- Mold draining

Boe-Therm A/S Industrivænget 1 DK-5610 Assens +45 64 71 23 75 info@boe-therm.dk www.boe-therm.dk